

Ceiling Loudspeaker

TSG-CM6F

6W Metal Ceiling Loudspeaker with Optional Fire Dome

Metal ceiling speaker | 6" driver for speech and music reproduction | Optional fire dome for EVAC applications

Where safety is of utmost importance the TSG-CM6F is the perfect fit. Combining a 6" driver this speaker delivers great performance across the frequency spectrum. These speakers find their application in shopping malls, lecture halls, corporate offices, cafeterias, and venues that require good speech and music reproduction. The optional fire-dome is an accessory that can be added in-order to use the same speaker for EVAC purposes. The full metal fire dome provides added protection to the speaker in the event of a fire accident.

Technical Specifications

MODEL TSG-CM6F

Electrical


Rated power/Max. Power, W	6/9
Tappings 100 V line, W	6/3/1.5
Frequency range(-10dB), Hz	125 - 16000
Sensitivity @ 1m, 1W (dB)	92
SPL @ 1m, Rated power (dB)	96
Speaker unit size	6"
Dispersion Angle	170 deg

Mechanical


Dimensions, mm	200(OD) X 75(H)
Color	Opal White
Weight, Kg	0.730
Material	Metal
Mounting	Spring clamp
Cut-out, mm	Ø170



Circuit Diagram



Frequency Response



Ceiling Loudspeaker



Optional **Fire-dome**

Part Code : **TSG-FD6**



For more information, contact techsupport@tsgaudioinnovation.com